



## EMS-SKLU

### 6th Gen Intel®Core™ Processor i7/i5/i3/Celeron Fanless Rugged Embedded System

- > Onboard 6th Gen Intel® Core™ SoC i7/i5/i3/Celeron BGA Processor
- > One 260-pin SODIMM Socket Up to 16GB DDR4 2133MHz SDRAM
- > Expansion Slot Supports 1 Mini PCIe Slot, 1 M.2, 1 IET Interface
- > Front Access Swappable 2.5" Drive Bay, 2 SIM Card
- > Rugged Design for Vibration & Shock Protection
- > Fanless Operating from -20 ~ 60°C, Support IP50
- > Power Input: Typical 12/24 Vdc ( +9~ 32V )
- > Supports Intel® iAMT 11.0, TPM2.0 , Turbo Boost Technology, vPro, Wake on LAN
- > Service Window, Easy to Install M.2, Memory and Mini PCIe Module

#### + Spec

System	
<b>Processor</b>	6th Gen Intel® Core™ i7-6600U, 2-Core, 2.6GHz processor 6th Gen Intel® Core™ i5-6300U, 2-Core, 2.4GHz processor 6th Gen Intel® Core™ i3-6100U, 2-Core, 2.3GHz processor
<b>System Memory</b>	1 x 260-Pin DDR4 2133MHz SO-DIMM up to 16 GB
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec.
<b>H/W Status Monitor</b>	Monitoring CPU & System Temperature and Voltage
<b>Board</b>	EBM-SKLUS
Expansion	
<b>Expansion</b>	1 x Avalue 80-Pin IET Interface 1 x Mini PCIe 1 x M.2 (B-Key, 2242, 3042)
Storage	
<b>Storage</b>	1 x 2.5" Drive Bay 1 x M.2 (SATA)
I/O	
<b>USB</b>	4 x USB 3.0
<b>COM Port</b>	2 x RS-232/422/485 (Jumper)
<b>DIO</b>	1 x 12bit GPIO
<b>Other</b>	2 x SIM Card Slot 1 x SMBus 2 x PS2/ KB & MS 2 x Knockouts for Antenna Mounting
Display	
<b>Chipset</b>	Intel® Skylake SoC integrated Graphics
<b>Resolution</b>	DP: Max. resolution 4096x2304 @ 60Hz
Audio	
<b>Chipset</b>	Realtek ALC892 supports 2.1-CH
<b>Audio Interface</b>	Mic-In, Line-In and Line-Out
Ethernet	
<b>Chipset</b>	1 x Intel® I211AT 1 x Intel® I219LM
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ-45
Mechanical & Environmental	
<b>Operating Temp</b>	(w/SSD), ambient w/ air flow -20°C ~ 60°C (-4°F ~ 140°F) (w/HDD), ambient w/ air flow 0°C ~ 40°C (32°F ~ 104°F)
<b>Storage Temp</b>	-40°C ~ 75°C (-40°F ~ 167°F)
<b>Operating Humidity</b>	0% ~ 90% Relative Humidity, Non-condensing
<b>Construction</b>	Aluminum + Metal
<b>Mounting Kit</b>	Wall Mount kit (Standard)
<b>Dimension (L x W x H)</b>	9.45" x 6.69" x 1.77" (240mm x 170mm x 45mm)
<b>Vibration Test</b>	With SSD : 5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 1hr/axis
<b>Shock Test</b>	With SSD : 50Grms, IEC 60068-2-27, Half Sine, 11ms
Certifications	
<b>Certification Information</b>	CE / FCC Class A
Software Support	



<b>OS Information</b>	Win 10 / Win 8.1 / Win 7 / Linux
<b>Power Requirement</b>	
<b>Power Connector</b>	3-Pin Terminal Block
<b>Power Requirement</b>	Power input: Typical 12/24Vdc(+9V ~ +32V) TVS component for surge protection Reverse current/voltage protection
<b>ACPI</b>	Single Power ATX Support S0, S3, S4, S5 ACPI 5.0 Compliant
<b>Power Mode</b>	AT/ATX (ATX is default setting)
<b>Adapter</b>	Optional AC-DC Adapter

 Ordering

EMS-SKLU-66-A1-1R  
6th Gen Intel®Core™ Processor i7-6600U Fanless Rugged Embedded System

EMS-SKLU-66-A1-5R  
6th Gen Intel®Core™ Processor i7-6600U Fanless Rugged Embedded System with 4 LAN PoE