



REV	ECN NO.	CONTENT	CHK	DATE

NOTES:

1. Rating: 300V/16A <IEC> 320V/20A
- 2.Poles:02-24P
3. Insulation Withstands Voltage: AC2000V/1 Min
- 4.Contact resistance: 20mΩ
5. Insulation Resistance: 500MΩ at DC500V
6. Using Temperature Range: -40°C/+115°C
7. Max soldering : +250° for SS
8. RoHS Compliance.
- 9.'With' ★ "is important dimension

How to order

ULO-TB21 - 2YC/5.0 - P - Y 0 0 0 A

Certificate Factory poles color: Customer requirements
 Series NO. Code 1:Grey 2:Blue 3:Black 4:Green 5:Orange 6:Red 7:transparent 8:Yellow 9:White

Total Pitch Tolerances				Nominal dimension range				≡	≠	—	//
0	30	53	70	90	115	150	200	250	0	0	100
over	to	to	to	to	to	to	to	to	to	all	to
±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.55	±0.70	±0.75	±0.20	±0.25	±0.30
±0.35	±0.44	±0.55	±0.70	±0.75	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3
6	5	4	3	2	1	1	1	1	1	1	1

2	Solde pin	314.00000011/12	N	BRASS	Sn Plated
1	Housing	4030001240	1	PA66	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	DATE	18.10.17	UNITS	MM	SHEET/OF
CHK.	DATE		SCALE	1:1	A4
APP.	DATE				1/1
NINGBO ULO ELECTRONICS CO., LTD.					
DWGNO: ULOTR21Y000A					