

MTX-ROUTER-HELIOS II

Industrial LTE Router 4 Ethernet ports GPS and WiFi

The MTX-Router-Helios II is the new LTE industrial router developed for industrial applications. The router has some special features that make this device the perfect solution for harsh environments such as in-vehicle use, factory, traffic panel information systems, wind and solar farms, etc.

Plenty of interfaces: 4 x Ethernet, WiFi 802.11n, USB, RS232, Dual SIM it can be used for many different M2M and IoT applications. A LTE modem is attached internally.

The MTX-Router-Helios II also includes advanced functionalities such as: DHCP server, NAT, QoS, Firewall, WiFi access point, captive portal, 4G to RS232 gateways, Modbus RTU to Modbus TPC gateway, VPN tunneling (IPsec, PPTP, GRE and open VPN), DynDNS/NoIP client, digital I/O control, remote firmware upgrade, among others.




MAIN FEATURES




4G connectivity



WiFi b/g/n access point



Ethernet



USB/RS232 RS485



Extended temperature



DIO



DynDNS/No-IP compatible



SMS alarms and control



Firewall



Web server



GPS

-  DC: 9-48 Vdc
-  Temperature range: -20° to +70°C
-  Dimensions: 187x110x31mm
-  Weight: <600gr

Preliminary Datasheet. Subject to changes | 2017/09
MTX © by MATRIX ELECTRONICA S.L.U.
mtxm2m.com



HARDWARE FEATURES

MTX-ROUTER-HELIOS II 4G



LTE 800, 900, 1800, 2600MHz; UMTS/HSPA+ 900, 2100MHz

4G

LTE Cat.4 FDD: B1, B3, B7, B8, B20: DL 150Mbps, UL 50Mbps; MIMO

3G

HSPA (3GPP release 6, 7) B1, B8: DL 7.2Mbps, UL 5.7Mbps; HSDPA Cat.8/HSUPA Cat.6 data rates

2G

GPRS B3, B8: Class 12; mobile station class B; PBCCH support; coding schemes CS 1-4



BD/GLONASS/GPS

General Features



4G connectivity supervisor to maintain connection always active



DHCP server



Captive portal with radius authentication



NAT/IP firewall



QoS



Modbus TCP to Modbus RTU



Serial tunnelling



DynDNS, NoIP



Programmable autoreset



VPN tunneling (IPsec, PPTP, GRE and open VPN)



VLAN management



Remote management (web, SSH, Telnet)



Remote firmware upgrade



Power adapter, wallmount and DIN rail kits included

Interfaces



4x ethernet 10/100 BaseT (RJ45 connector)



Internal WiFi 802.11 b/g/n optional



USB, 1x RS232 4-wire and RS485/232 2-wire



2x digital input/output



Operating LEDs



Dual SIM card interface 1.8V/3V



Console port connector



5x SMA antenna connectors



Terminal block for power redundant power input

Ordering Information

MTX-Router-Helios II LTE WiFi
GPS 4xETH

502300041