


# IC0300-83B

Robust DIN-rail Fanless Embedded System with Intel® Celeron® Processor N3350/  
Pentium® Processor N4200, Isolated COM, LAN and DIO

## Features


- Cost-effective with fanless and cableless design
- Intel® Celeron® processor N3350/Pentium® processor N4200
- 2 or 4 isolated COM, 4 USB, 2 GbE LAN
- 8-bit programmable DIO for IoT gateway applications (optional)
- Wide operating temperature range from -40°C to +70°C
- 12 to 24 VDC wide range power input
- OVP, UVP, OCP, RPP power protection design
- AMS.AXView intelligent remote monitoring software for IIoT



▲ Front view



▲ Rear view



▲ Top view



## Specifications

Standard Color	Silver
Construction	Extruded aluminum and heavy-duty steel, IP40
CPU	Intel® Celeron® processor N3350 (1.1 GHz, Dual Core) Intel® Pentium® processor N4200 (1.1 GHz, Quad Core) (by request)
System Board	SBC8783B
System Memory	1 x DDR3L-1866 SO-DIMM, up to 8GB
BIOS	AMI UEFI BIOS
System I/O Outlet	Serial 4 x isolated RS-232/422/485 (IC0300-83B-4I COM) 2 x isolated RS-232/422/485 (IC0300-83B-2I COM) 4 x RS-232/422/485 (IC0300-83B-4 COM) COM port support High-speed mode up to 1.5M baud rate Interface select by BIOS Supports Auto Flow Control in RS-485 mode
USB	4 x USB 3.0
RTC	Battery onboard
Storage	2.5" SATA drive (9.5 mm height) mSATA shared with mPCIe slot
LAN	2 x 10/100/1000 Mbps Ethernet (Intel® i211-AT for IC0300-83B) (Intel® i210-IT for IC0300-83B-WT)
Display	1 x VGA or 1 x HDMI
DIO	1 x DI/DO (8-bit programmable, DB9 female connector, optional) Voltage is 5V TTL-level Programming: I/O sink current is 10mA (max.) Input/output can be programming
Power Input	1 x DC power input with terminal block

Extension Interface	1 x Full-size PCI Express Mini Card slot with SIM slot (for wireless module) 1 x Full-size PCI Express Mini Card slot with mSATA (for wireless module or mSATA)
Watchdog Timer	255 levels, 1 to 255 sec.
System Indicator	Power, Active
Power Supply	12 to 24 VDC, 2.82 to 1.34A (IC0300-83B-N3350) 12 to 24 VDC, 3.27 to 1.62A (IC0300-83B-N4200) Protection: OVP (±20%), reverse protection
Operating Temperature	-20°C to +70°C (-4°F to +158°F) (IC0300-83B-N3350) -40°C to +70°C (-4°F to +158°F) (IC0300-83B-N3350-WT) -40°C to +60°C (-4°F to +140°F) (IC0300-83B-N4200-WT)
Humidity	10% to 95%
Vibration Endurance	2 Gms (5 to 500Hz, amplitude 0.35 mm; operation/storage/transport)
Weight (net/gross)	1.0 kg (2.2 lb)/1.50 kg (3.3 lb)
Certifications	CE, FCC
Dimensions	48 mm (1.88") (W) x 110 mm (4.33") (D) x 155 mm (6.1") (H)
EOS Support	Windows® 10 IoT, Linux support package (by request)
Software Support	AMS.AXView


## Ordering Information

Standard	
IC0300-83B-N3350-4ICOM-WT-DC (P/N: E22C300119)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 4 isolated COM, 2 LAN, 4 USB and VGA (-40°C to +70°C)
IC0300-83B-N4200-4ICOM-WT-DC (P/N: E22C300120)	Robust DIN-rail fanless embedded system with Intel® Pentium® processor N4200, 4 isolated COM, 2 LAN, 4 USB and VGA (-40°C to +60°C)
IC0300-83B-N3350-4COM-DC (P/N: E22C300121)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 4 COM, 2 LAN, 4 USB and VGA (-20°C to +70°C)
IC0300-83B-N3350-4ICOM-DC (P/N: E22C300123)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350 1.1 GHz, 4 isolated COM, 2 LAN, 4 USB and VGA (-20°C to +70°C)
IC0300-83B-N3350-2ICOM-HDMI-DC (P/N: E22C300124)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350 1.1 GHz, 2 isolated COM, 2 LAN, 4 USB and HDMI (-20°C to +70°C)
IC0300-83B-N3350-4ICOM-WT-HDMI-DC (P/N: E22C300126)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350 1.1 GHz, 4 isolated COM, 2 LAN, 4 USB and HDMI (-40°C to +70°C)
IC0300-83B-N3350-2ICOM-DC (P/N: E22C300127)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 2 isolated COM, 2 LAN, 4 USB and VGA (-20°C to +70°C)
IC0300-83B-N3350-4COM-HDMI-DC (P/N: E22C300128)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 4 COM, 2 LAN, 4 USB and HDMI (-20°C to +70°C)
IC0300-83B-N3350-4ICOM-DIO-DC (P/N: E22C300137)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 4 isolated COM, 2 LAN, 4 USB, DIO and VGA (-20°C to +70°C)
IC0300-83B-N3350-4COM-DIO-DC (P/N: E22C300138)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 4 COM, 2 LAN, 1 DIO, 4 USB and VGA (-20°C to +70°C)
IC0300-83B-N3350-2COM-2CAN-DC (P/N: E22C300143)	Robust DIN-rail fanless embedded system with Intel® Celeron® processor N3350, 2 COM, 2 LAN, 2 CAN, 4 USB and VGA (-20°C to +70°C)

Optional	
mSATA	4GB and above
2.5" SATA drive	
DDR3L SO-DIMM	2GB to 8GB
8812C3000A0E	IC0300/310/320 wall mount bracket kit
8816N3235A0E	3G/GPS UC20G kit for tBOX (3G/GPS ANT) (E)

\* Specifications and certifications may vary based on different requirements.

## Dimensions



(IC0300-83B-DIO)

