

### Key Features:

- 15" medical display with 1024 x 768 (4:3) resolution
- 5-Wire resistive touch with USB/RS232 combo touch interface
- 350 nits screen brightness with high contrast display
- World class medical safety regulations and certifications
- Life cycle management and revision control



### Specifications

Specifications		
Panel Spec	Model Number	CM-ME150R35XG
	Resolution	1024 (H) x 768 (V)
	Screen Size (inch)	15
	Display Area (mm)	304.1(H) x 228.1(V)
	Pixel Pitch (mm)	0.297 (H) x 0.297 (V)
	Viewing Angle (degree)	160 (H)/150 (V)
	Response Time (ms)	8 (on/off)
	Brightness (cd/m <sup>2</sup> )	350 (typ.)
	Contrast Ratio	800:1 (typ.)
	Color Depth (bits)	6+FRC (16.2M)
I/O Interface	DVI	1x DVI-D
	DP	N/A
	VGA	1x D-Sub15
	HDMI	N/A
	Audio	3.5mm
Touch	Type	5-Wire Resistive
	Touch Point	1
	Screen Printing	N/A
	Glass Coating	AG
	Interface	Combo (USB/RS232)

Specifications		
Features	Color Temperature	Neutral/Warm/Cool/User
	Gamma Selection	1.8/2.0/2.2/DICOM
	Gamma LUT (bits)	10
	OSD Languages	English/French/German/Italian/Spanish/Japanese
	Speaker	2W Speaker
	Scaling Mode	N/A
Power	Power Supply	AC 100~240V/DC 12V
	Power Consumption (W)	25 (Max)
Physical Characteristics	Dimension: (W×H×D)(mm)	347.4 x 355.7 x 175 (with Stand) 347.4 x 271.4 x 58 (w/o Stand) 333.4 x 259.2 x 51 (Open-Frame w/o Touch)
	VESA Mounting (mm)	75 x 75 / 100 x 100
	Weight (Kg)	5.6 (w/ Stand)
		3.8 (w/o Stand)
		3.1 (Open-Frame)
	ID Color	White/Black
	IP Rating (Front)	NA
	IP Rating (Back Cover)	IPX1
	Tilt Range (degree)	0~+30
	Pivot Range (degree)	NA
Swivel Range (degree)	NA	
Height Adjustment (mm)	NA	
Reliability	Operating Temperature(°C)	10 to 40
	Operating Humidity (RH)	30% to 75%
	Storage Temperature (°C)	-20 to 60
	Storage Humidity (RH)	10% to 90%
<b>Certifications</b>	UL/cUL (60601 Ed3.1),CB (60601 Ed3.1),CE,FCC-B,VCCI-B	
<b>Warranty</b>	3 years	