

MTX-Router-EOS

LTE/4G, dual SIM & 3x Ethernet compact industrial IoT router

The MTX-Router-EOS is an entry level router developed for industrial applications. It has a very compact design with a very rugged enclosure and accessories to be mount in a wall mount. It features dual SIM, 3x Ethernet, VPN client and 3 antennas included (another one for GPS optional). The MTX-Router-EOS can be used in many different IOT applications like kiosk, telemetry, remote sensing, smart grid, security, industrial automation, etc.



MAIN FEATURES



4G



Dual SIM



WiFi



3x Ethernet



RS232/
RS485



DIN rail



Modbus



VPN



DHCP



Firewall



Serial
tunnelling



DynDNS



Programmable
autoreset



MQTT



SMS
control

CERVELLO STEM - IOT PLATFORM FREE FOR ONE YEAR WITH THIS DEVICE



Devices
inventory



Rules engine



Command
template







Remote Control



Real time
Dashboards



Custom
admin role

-  DC input: 5-35 Vdc Phoenix type
-  Temperature range: -35° to +75°C
-  Dimensions: 115x97x24mm
-  Weight: 390gr

Preliminary Datasheet. Subject to changes | 2020/05
MTX © by MATRIX ELECTRONICA S.L.U.
SUPPORT: iotsupport@mtx2m.com
SALES: info@mtx2m.com
mtx2m.com

HARDWARE FEATURES

MTX-ROUTER-EOS 4G



LTE 700, 800, 900, 1800, 2600MHz; UMTS/HSPA+ 900, 2100MHz

4G


LTE Cat.4 FDD: B1, B3, B7, B8, B20, B28A: DL 150Mbps, UL 50Mbps; MIMO

3G


HSPA (3GPP release 6, 7) B1, B8: DL 7.2Mbps, UL 5.7Mbps; HSDPA Cat.8/HSUPA Cat.6 data rates

2G

GPRS B3, B8: Class 12; mobile station class B; PBCCH support; coding schemes CS 1-4



LTE main, LTE div, WiFi, DC Power, Dual SIM



Status LEDs

Interfaces



4G/3G/2G connectivity



3x Ethernet 10/100 BaseT



1x COM (RS232 or RS485)



WiFi 802.11 b/g/n



GPS (optional)



Operating LEDs



SIM card interface 1.8V/3V



DIN rail

Connectors



3x RJ45: Ethernet 10/100 BaseT



1x terminal block: RS232/485



Dual SIM card



2x SMA F antenna connectors: LTE



1x SMA F RP antenna connector: WiFi



1x SMA F antenna connectors: GPS (optional)



DC power terminal block: power input

Packing List Included



DIN rail and wallmount kits



Ethernet cable












WiFi antennas



LTE antennas

SOFTWARE FEATURES

-  DHCP server
-  NAT/IP firewall
-  Serial tunnelling
-  Multiple DDNS provider supported
-  Automatic data sending (MQTT)
-  Schedule reboot, schedule online and off-line
-  SMS control
-  Remote management (web, SSH, Telnet)
-  Remote firmware upgrade

ORDERING INFORMATION



MTX-Router-EOS 4G WiFi

502300047










CERVELLO STEM - IOT PLATFORM


FREE FOR ONE YEAR WITH MTX DEVICES**






General Features

-  Up to unlimited devices
-  Rules engine
-  Real time dashboards
-  Remote control
-  Multi-tenant*
-  White labeling*
-  Custom admin role*



Control

-  Command template




Devices Inventory

-  Add single and single from template
-  Add Bulk from template and from autoprovisioning
-  Manage: Device template, Groups, Assets and Bulk actions

Visualize

-  Dashboards
-  Reports

Security

-  2-factor authentication
-  SSL for end user application
-  Custom admin roles*

*Upgrade required

**Available with compatible devices: MTX-EOS and MTX devices with MTX-Tunnel or MTX-Titan



Preliminary datasheet. Subject to changes | 2020/05 | MTX-Router-EOS

MTX © by MATRIX ELECTRONICA S.L.U.

SUPPORT: iotsupport@mtxm2m.com | SALES: info@mtxm2m.com | mtxm2m.com