

D

8025-YH1

80x80x25mm(3.15"x3.15"x0.98")



Thermoplastic PBT, UL94V-0
 Thermoplastic PBT, UL94V-0
 Ball or Sleeve
 -10°C to +70°
 5mA Max. at 500 VAC for 1 minute
 10M Ω min. @500 VDC
 72g
 Yes
 IP21 (Special IP Rating On Request)

80

 mm

SPECIFICATION

MODEL NO.	RATED VOLTAGE(V)	RATED CURRENT(A)	INPUT POWER(W)	SPEED (RPM)	MAX. AIR PRESSURE		MAX. AIR FLOW		NOISE dB(A) @1M
					inchH2O	mmH2O	CFM	m3/min	
D8025V48H-YH1	48	0.06	2.88	3500	0.19	4.80	42.37	1.20	38.5
D8025V48SL-YH1	48	0.09	4.32	4000	0.24	6.12	48.53	1.37	41.0
D8025V48SM-YH1	48	0.10	4.80	4500	0.30	7.64	54.67	1.55	44.3
D8025V24L-YH1	24	0.07	1.68	2500	0.10	2.64	30.54	0.86	28.9
D8025V24M-YH1	24	0.11	2.64	3000	0.14	3.59	36.46	1.03	33.8
D8025V24H-YH1	24	0.13	3.12	3500	0.19	4.80	42.37	1.20	38.5
D8025V24SL-YH1	24	0.16	3.84	4000	0.24	6.12	48.53	1.37	41.0
D8025V24SM-YH1	24	0.23	5.52	4500	0.30	7.64	54.67	1.55	44.3
D8025V12L-YH1	12	0.14	1.68	2500	0.10	2.64	30.54	0.86	28.9
D8025V12M-YH1	12	0.20	2.40	3000	0.14	3.59	36.46	1.03	33.8
D8025V12H-YH1	12	0.26	3.12	3500	0.19	4.80	42.37	1.20	38.5
D8025V12SL-YH1	12	0.32	3.84	4000	0.24	6.12	48.53	1.37	41.0

DIMENSION



