

Shenzhen Top Power Co., Ltd.

Add:3/F.,Bldg.B5,Junfeng Industrial Park,Yonghe Road,Heping,Fuyong,Shenzhen

Tel:+86-755-23359172 29919580 Fax:+86-755-29919580

<http://www.sz-toppower.com>

Contact:Henry Email:henry@sz-toppower.com Skype:toppower.henry

15w eu catalogue

Item	Description	Photo
1	<p>Model Name: TPS-0501000EU(5V 1A), TPS-0501500EU(5V 1.5A), TPS-0502000EU(5V 2A), TPS-0502500EU(5V 2.5A), TPS-0601000EU(6V 1A), TPS-0602000EU(6V 2A), TPS-0900500EU(9V 0.5A), TPS-0901000EU(9V 1A), TPS-0901500EU(9V 1.5A), TPS-1200500EU(12V 0.5A), TPS-1201000EU(12V 1A), TPS-1201250EU(12V 1.25A), TPS-1500500EU(15V 0.5A), TPS-1501000EU(15V 1A), TPS-1800500EU(18V 0.5A), TPS-1900500EU(19V 0.5A), TPS-2000500EU(20V 0.5A), TPS-2400500EU(24V 0.5A),</p> <p>Rated Output Power: 15W Max. Output Voltage & Current : 5Vdc-24Vdc, 0.01A-2.5A AC plug: EU 2pin plug Dimension : 71.8*43*31.5 (mm) Certification: CE,ROHS Efficiency: Level V Input Voltage: 100-240Vac Variation Range: 90-264Vac Load Regulation: $V_{out} \pm V_{out} * 5\%$ Ripple And Noise(Max.): no more than 120mVp-p Turn On Delay Time: 3 second Max. At 230VAC Rise Time: 100mS Max. At 230Vac Hold Up Time: 7mS Min. At 230Vac Protection: OTP/OCP/OVP/SCP Operating Temperature: 0°C to 40°C, Full load, Normal Storage Temperature: -20°C to 85°C Relative Humidity: 5%(0°C)~90%(40°C)RH, 72Hrs, Full load, Normal operating Vibration: Operating: IEC 721-3-3 3M3/IEC 721-3-2 2M2/Axes, 10 cycles per axis/Dropping tests: 1 corner, 3 edges, and 6 surfaces one time for each surface (DIELECTRIC STRENGTH)(Hi-Pot): (Primary to secondary), 3000Vac/10mA/1Min. Surge immunity with 1K voltage</p>	

Remark:

- 1 The DC cable length can be 1.2m, 1.5m, 1.8m, 2.0m, 2.5m, 3.0m.
- 2 DC plug size can be 5.5*2.1*10 or 5.5*2.5*10 (mm).
- 3 Price will be calculated based on your specific details requirements.
- 4 Payment terms: 30% T/T as deposit, 70% T/T before loading!
- 5 Lead time: 35-40 days after get the deposit!