

General Description


These N-Channel enhancement mode power field effect transistors are planar stripe, DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency switch mode power supply

BVDSS	RDSON	ID
500V	320mΩ	18A

Features

- 500V, 18A, $RDS(ON) = 320m\Omega @ VGS = 10V$
- Improved dv/dt capability
- Fast switching
- 100% EAS Guaranteed
- Green Device Available

TO247 Pin Configuration



Absolute Maximum Ratings $T_c=25^\circ C$ unless otherwise noted

Symbol	Parameter	Rating	Units
V_{DS}	Drain-Source Voltage	500	V
V_{GS}	Gate-Source Voltage	± 30	V
I_D	Drain Current – Continuous ($T_c=25^\circ C$)	18	A
	Drain Current – Continuous ($T_c=100^\circ C$)	11.5	A
I_{DM}	Drain Current – Pulsed ¹	72	A
EAS	Single Pulse Avalanche Energy ²	2000	mJ
IAS	Single Pulse Avalanche Current ²	20	A
P_D	Power Dissipation ($T_c=25^\circ C$)	379	W
	Power Dissipation – Derate above $25^\circ C$	3.03	W/ $^\circ C$
T_{STG}	Storage Temperature Range	-55 to 150	$^\circ C$
T_J	Operating Junction Temperature Range	-55 to 150	$^\circ C$

Thermal Characteristics

Symbol	Parameter	Typ.	Max.	Unit
$R_{\theta JA}$	Thermal Resistance Junction to ambient	---	62	$^\circ C/W$
$R_{\theta JC}$	Thermal Resistance Junction to Case	---	0.35	$^\circ C/W$



500V N-Channel MOSFETs

PMX18N50P

Electrical Characteristics ($T_J=25\text{ }^{\circ}\text{C}$, unless otherwise noted)**Off Characteristics**

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
BV_{DSS}	Drain-Source Breakdown Voltage	$V_{\text{GS}}=0\text{V}$, $I_{\text{D}}=250\mu\text{A}$	500	---	---	V
I_{DSS}	Drain-Source Leakage Current	$V_{\text{DS}}=500\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=25\text{ }^{\circ}\text{C}$	---	---	1	μA
		$V_{\text{DS}}=400\text{V}$, $V_{\text{GS}}=0\text{V}$, $T_J=100\text{ }^{\circ}\text{C}$	---	---	20	μA
I_{GSS}	Gate-Source Leakage Current	$V_{\text{GS}}=\pm 30\text{V}$, $V_{\text{DS}}=0\text{V}$	---	---	± 100	nA

On Characteristics

$\text{R}_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{\text{GS}}=10\text{V}$, $I_{\text{D}}=2\text{A}$	---	260	320	$\text{m}\Omega$
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{\text{GS}}=V_{\text{DS}}$, $I_{\text{D}}=250\mu\text{A}$	2.5	3.5	4.5	V
gfs	Forward Transconductance	$V_{\text{DS}}=30\text{V}$, $I_{\text{D}}=5\text{A}$	---	9	---	S

Dynamic and switching Characteristics







Q_g	Total Gate Charge ^{3,4}	$V_{\text{DS}}=350\text{V}$, $V_{\text{GS}}=10\text{V}$, $I_{\text{D}}=9\text{A}$	---	88	135	nC
Q_{gs}	Gate-Source Charge ^{3,4}		---	17	25	
Q_{gd}	Gate-Drain Charge ^{3,4}		---	47	70	
$T_{\text{d(on)}}$	Turn-On Delay Time ^{3,4}	$V_{\text{DD}}=350\text{V}$, $V_{\text{GS}}=10\text{V}$, $R_{\text{G}}=25\Omega$ $I_{\text{D}}=9\text{A}$	---	60	90	ns
T_r	Rise Time ^{3,4}		---	90	135	
$T_{\text{d(off)}}$	Turn-Off Delay Time ^{3,4}		---	240	360	
T_f	Fall Time ^{3,4}		---	70	105	
C_{iss}	Input Capacitance	$V_{\text{DS}}=25\text{V}$, $V_{\text{GS}}=0\text{V}$, $F=1\text{MHz}$	---	3400	5100	pF
C_{oss}	Output Capacitance		---	275	415	
C_{rss}	Reverse Transfer Capacitance		---	32	50	
R_g	Gate resistance	$V_{\text{GS}}=0\text{V}$, $V_{\text{DS}}=0\text{V}$, $F=1\text{MHz}$	---	2	---	Ω







Drain-Source Diode Characteristics and Maximum Ratings

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
I_s	Continuous Source Current	$V_G=V_D=0\text{V}$, Force Current	---	---	18	A
I_{SM}	Pulsed Source Current		---	---	36	A
V_{SD}	Diode Forward Voltage	$V_{\text{GS}}=0\text{V}$, $I_s=18\text{A}$, $T_J=25\text{ }^{\circ}\text{C}$	---	---	1.3	V
t_{rr}	Reverse Recovery Time	$V_R=400\text{V}$, $I_s=5\text{A}$ $dI/dt=100\text{A}/\mu\text{s}$, $T_J=25\text{ }^{\circ}\text{C}$	---	340	---	ns
Q_{rr}	Reverse Recovery Charge		---	3.8	---	uC


Note :

- Repetitive Rating : Pulsed width limited by maximum junction temperature.
- $V_{\text{DD}}=50\text{V}$, $V_{\text{GS}}=10\text{V}$, $L=10\text{mH}$, $I_{\text{AS}}=20\text{A}$, $R_{\text{G}}=25\Omega$, Starting $T_J=25\text{ }^{\circ}\text{C}$.
- The data tested by pulsed , pulse width $\leq 300\text{us}$, duty cycle $\leq 2\%$.
- Essentially independent of operating temperature.


Fig.1 Typical Output Characteristics

Fig.2 Continuous Drain Current vs. T_c

Fig.3 Normalized R_{DSON} vs. T_j

Fig.4 Normalized V_{th} vs. T_j

Fig.5 Turn-On Resistance vs. V_{GS}

Fig.6 Turn-On Resistance vs. I_D


Fig.7 Capacitance Characteristics

Fig.8 Gate Charge Characteristics

Fig.9 Normalized Transient Impedance

Fig.10 Maximum Safe Operation Area

Fig.11 Switching Time Waveform

Fig.12 EAS Waveform

TO247 PACKAGE INFORMATION



SYMBOL	mm		SYMBOL	mm	
	MIN	MAX		MIN	MAX
A	4.83	5.21	E2	4.32	5.49
A1	2.29	2.55	E3	2.15	2.80
A2	1.50	2.49	e	5.44BSC	
b	1.12	1.33	L	19.81	20.32
b1	1.91	2.39	L1	4.10	4.40
b2	2.87	3.22	ØP	3.56	3.65
C	0.55	0.69	Q	5.39	6.20
D	20.80	21.10	S	6.04	6.30
D1	16.25	17.65			
D2	0.51	1.35			
E	15.75	16.13			
E1	13.46	14.16			