

TAU1113


GNSS Positioning Module

Industrial

PRODUCT DESCRIPTION

TAU1113 is a cost-effective low-power GNSS positioning module based on CYNOSURE III Lite GNSS SoC chip. It supports GPS/QZSS, BDS, Galileo, GLONASS and SBAS. The module features SAW, LNA, flash memory as well as an antenna supervisor in a compact form factor.

TAU1113 is a versatile receiver that can be used with active and passive antennas, making it an excellent choice for a wide range of applications such as tracking, telematics and navigation. The fast start-up in combined with the low power consumption and the very low backup current make the TAU1113 particularly suitable for use in battery-powered devices, e.g., for asset tracking.



HIGHLIGHTS

- Versatile GNSS module supporting GPS/QZSS, BDS, Galileo, GLONASS and SBAS
- Low current consumption of only 16 mA for GPS/QZSS
- Backup current of only 15 μ A
- Active and passive antennas supported thanks to built-in SAW and LNA
- Supports Allystar's free-of-charge A-GNSS service for minimal startup times
- Pin-compatible with previous generation TAU1103, TAU1105 and many mainstream GNSS modules

APPLICATIONS



Bike Sharing



Asset Tracking



Fleet Management



Telematics

Product Selector:

Product Model	GNSS							Feature					Interface			Accuracy			Grade		
	GNSS system mode	Band(S/D/T)	GPS/QZSS	BDS	GLONASS	Galileo	NavIC	SBAS	Built-in LNA	Programmable (Flash)	Data Logging	D-GNSS	Oscillator	UART	I2C	USB	SPI	Meter	Sub-Meter	Centi-Meter	Industrial
TAU1113	01	S	•		•			•	•	•	•	T	•				•			•	
	02	S	•		•	•		•	•	•	•	T	•				•			•	
	03	S	•	•		•		•	•	•	•	T	•				•			•	

T = TCXO

GENERAL SPECIFICATIONS

GNSS Engine

Cynosure III Lite GNSS Engine
 Total 88 GNSS channels
 5 Hz maximum update rate

GNSS Reception

GPS/QZSS: L1C/A
 Galileo: E1
 GLONASS: G1
 BDS: B1I
 SBAS: L1

Position Accuracy*

GNSS	1.5m CEP
GNSS (with SBAS)	< 1.0m CEP

* Open sky condition.

Sensitivity*

Cold Start	-148 dBm
Hot Start	-156 dBm
Reacquisition	-158 dBm
Tracking	-163 dBm

* Demonstrated with a good external LNA.

Velocity & Time Accuracy

GNSS	0.1 m/s CEP
1PPS	20 ns

Interfaces

UART	1
------	---

Time to First Fix (TTFF)

Supporting system	Hot start	Cold start
GPS/QZSS+Galileo+GLONASS+SBAS	2s	26s
GPS/QZSS+GLONASS+SBAS	2s	28s
GPS/QZSS+Galileo+BDS+SBAS	2s	28s
GPS/QZSS	1s	28s

Operating Condition

Main voltage	2.0-3.63 V
Digital I/O voltage	2.0-3.63 V
Backup voltage	1.8-3.63 V

Operation Limit

Velocity	515 m/s
Altitude	18,000m

Antenna

Active antenna
 Passive antenna

Antenna Supervision

Antenna short circuit protection and open circuit detection

Power Consumption

Tracking	GPS/QZSS+GLONASS+SBAS	20 mA @ 3.3V
	GPS/QZSS+Galileo+BDS+SBAS	17 mA @ 3.3V
	GPS/QZSS	16 mA @ 3.3V
Standby	15 uA @ 3.3V	

ENVIRONMENT DATA

Operation temperature	-40°C to +85°C
Storage temperature	-40°C to +85°C
Certification	RoHS, REACH, FCC, CE-RED

PACKAGE

Package	18 PIN LCC
Dimensions	10.1*9.7*2.5 mm



Website: www.allystar.com

Email: info.gnss@allystar.com

Headquarters: 201-2, 2F, Tower F, Xinghe World, No.1, Yabao Road, LongGang District, Shenzhen City, Guangdong Province, China.

Calgary office: Unit 288, 3553 31 Street NW Calgary, Alberta, Canada T2L 2K7

This document contains proprietary technical information which is the property of ALLYSTAR Technology, copying of this document and giving it to others and using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. ALLYSTAR Technology reserves the right to make changes in its products, specifications and other information at any time without notice. For more documents, please visit www.allystar.com.