


# TAU1114

GNSS Positioning Module

Industrial

## PRODUCT DESCRIPTION

TAU1114 is a cost-effective GNSS positioning module based on CYNOSURE III Lite GNSS SoC chip supporting GPS/QZSS, BDS, Galileo, GLONASS and SBAS at a low current consumption. It is a versatile module that features SAW, LNA, flash memory as well as an antenna supervisor and can be used with active and passive antennas.



TAU1114 is fit for a wide range of applications in tracking, telematics, and navigation. It is pin compatible with its predecessors TAU1102 and TAU1111 as well as many mainstream GNSS modules, making it the perfect choice to upgrade existing design, be it for a lower power consumption or to avoid excessive lead times.

## HIGHLIGHTS

- Versatile GNSS module supporting GPS/QZSS, BDS, Galileo, GLONASS and SBAS
- Low current consumption of only 15 mA for GPS/QZSS
- Active and passive antennas supported thanks to built-in SAW and LNA
- Supports Allystar's free-of-charge A-GNSS service for minimal startup times
- Pin-compatible with previous generation TAU1102, TAU1111 and many mainstream GNSS modules

## APPLICATIONS



Bike Sharing



Asset Tracking



Fleet Management



Telematics

### Product Selector:

Product Model	GNSS							Feature					Interface			Accuracy		Grade				
	GNSS system mode	Band(S/D/T)	GPS/QZSS	BDS	GLONASS	Galileo	NavIC	SBAS	Built-in LNA	Programmable (Flash)	Data Logging	D-GNSS	Oscillator	UART	I2C	USB	SPI	Meter	Sub-Meter	Centi-Meter	Industrial	Automotive
TAU1114	01	S	•		•			•	•	•	•	•	T	•			•				•	
	02	S	•		•	•		•	•	•	•	•	T	•			•				•	
	03	S	•	•		•		•	•	•	•	•	T	•			•				•	

T = TCXO

## GENERAL SPECIFICATIONS

### GNSS Engine

Cynosure III Lite GNSS Engine  
Total 88 GNSS channels  
5 Hz maximum update rate

### GNSS Reception

GPS/QZSS: L1C/A  
Galileo: E1  
GLONASS: G1  
BDS: B1I  
SBAS: L1

### Position Accuracy\*

GNSS	1.5m CEP
GNSS (with SBAS)	< 1.0m CEP

\* Open sky condition.

### Sensitivity\*

Cold Start	-148 dBm
Hot Start	-156 dBm
Reacquisition	-158 dBm
Tracking	-163 dBm

\* Demonstrated with a good external LNA.

### Velocity & Time Accuracy

GNSS	0.1 m/s CEP
1PPS	20 ns

### Interfaces

UART	1
------	---

### Time to First Fix (TTFF)

Supporting system	Hot start	Cold start
GPS/QZSS+Galileo+GLONASS+SBAS	2s	26s
GPS/QZSS+GLONASS+SBAS	2s	28s
GPS/QZSS+Galileo+BDS+SBAS	2s	28s
GPS/QZSS	1s	28s

### Operating Condition

Main voltage	2.0-3.63 V
Digital I/O voltage	2.0-3.63 V
Backup voltage	1.8-3.63 V

### Operation Limit

Velocity	515 m/s
Altitude	18,000m

### Antenna

Active antenna  
Passive antenna

### Antenna Supervision

Antenna short circuit protection and open circuit detection

### Power Consumption

Tracking	GPS/QZSS+GLONASS+SBAS	20 mA @ 3.3V
	GPS/QZSS+Galileo+BDS+SBAS	16 mA @ 3.3V
	GPS/QZSS	15 mA @ 3.3V
Standby	15 uA @ 3.3V	

## ENVIRONMENT DATA

Operation temperature	-40°C to +85°C
Storage temperature	-40°C to +85°C
Certification	RoHS, REACH, FCC, CE-RED

## PACKAGE

Package	24 PIN LCC
Dimensions	12.2*16.0*2.4 mm



Website: [www.allystar.com](http://www.allystar.com)

Email: [info.gnss@allystar.com](mailto:info.gnss@allystar.com)

Headquarters: 201-2, 2F, Tower F, Xinghe World, No.1, Yabao Road, LongGang District, Shenzhen City, Guangdong Province, China.

Calgary office: Unit 288, 3553 31 Street NW Calgary, Alberta, Canada T2L 2K7

This document contains proprietary technical information which is the property of ALLYSTAR Technology, copying of this document and giving it to others and using or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the payment of damages. ALLYSTAR Technology reserves the right to make changes in its products, specifications and other information at any time without notice. For more documents, please visit [www.allystar.com](http://www.allystar.com).