



## ECM-EHL3

### Intel® Elkhart Lake 3.5" Micro Module

- > Bottom Layer Soldered Processor
- > Single DRAM Socket, Max, Up to 32GB DDR4 3200MTs (non-ECC Supported)
- > Triple Display, 2 x DP++, 1 x 2CH LVDS (share with eDP, default LVDS)
- > Triple Expansion Slot, M.2 Key-B, M.2 Key-E, M.2 Key-M
- > Three Gigabit Ethernet, 1 x 2.5GbE, 2 x 1GbE
- > Wide DC-Input, +9~36Vdc

#### + Spec

##### -System Information-

<b>Processor</b>	Onboard Intel® Pentium®/Celeron®/Atom™ SoC BGA Processor (Elkhart Lake Platform 4.5~12W)- (with CPU Bottom Mounted) Intel® Celeron® J6412 Processor (1.5M Cache, up to 2.60 GHz) Intel® Celeron® J6413 Processor (1.5M Cache, up to 3.00 GHz) Intel Atom® x6413E Processor (1.5M Cache, up to 3.00 GHz) Intel Atom® x6425RE Processor (1.5M Cache)
<b>Platform Controller Hub</b>	Elkhart lake SoC integrated
<b>System Memory</b>	Single 260-pin DDR4 SODIMM Socket, Supports Up to 32GB DDR4 3200MTs SDRAM
<b>I/O Chipset</b>	EC ITE IT571
<b>BIOS Information</b>	AMI BIOS, 256Mbit SPI Flash ROM
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec and 1sec. or 1min./step
<b>H/W Status Monitor</b>	CPU & system temperature monitoring Voltages monitoring
<b>TPM</b>	On board NuvoTon NPCT754AADYX support TPM 2.0

##### Expansion

<b>Expansion</b>	1 x M.2 Key E 2230 support WiFi module (PCI-e x1 & USB 2.0 Signal) 1 x M.2 Key B 3042/2242, standard package with 3042 to 3052 bracket + screw set (with SATA and USB3.0/USB2.0, with 1 x SIM card slot, support WWAN+GNSS or SSD) 1 x M.2 Key M support 2260 slot, standard package with 2260 to 2242 bracket + screw set (with 1 x PCI-e x1 signal)
------------------	---

##### Storage

<b>Storage</b>	1 x M.2 (Key-B) 1 x M.2 (Key-M) 1 x SATA III
----------------	--

##### I/O

<b>USB Port</b>	2 x USB 3.1 Gen2, 2 x USB2.0 at I/O 4 x USB2.0 by pin header
<b>COM Port</b>	2 x RS-232/422/485 4 x RS232
<b>SATA</b>	1 x SATA III
<b>DIO</b>	1 x 8-bit GPIO
<b>MIO</b>	1 x eSPI
<b>Other</b>	3 x LAN

##### Display

<b>Graphic Chipset</b>	Intel® UHD Graphics
<b>Spec. &amp; Resolution</b>	DP++ Max resolution 4096x2160@60Hz LVDS Max resolution 1920 x 1080 Dual channel 18/24-bits eDP1.3 Max resolution 4096x2160@60Hz
<b>Multiple Display</b>	Triple Display
<b>LVDS</b>	1 x LVDS: 1920 x 1080 Dual channel 18/24-bits LVDS (Chrontel CH7511B-BFI eDP to LVDS)share with eDP by switch IC, default LVDS

##### Audio

<b>Audio Codec</b>	Realtek ALC888S
<b>Audio Interface</b>	Line-out, Line-in, Mic-in
<b>Audio Amplifier</b>	3W Amplifier

##### Certifications

<b>Certification Information</b>	CE FCC Class B
----------------------------------	-------------------

##### Ethernet

<b>LAN Chipset</b>	Intel® I226LM, I210AT
<b>Ethernet Interface</b>	1 x 10/100/1000/2.5G Base-Tx GbE compatible 2x 10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	3 x RJ-45

##### Mechanical & Environmental

<b>Operating Temperature</b>	0°C ~ 60°C with 0.5m/s air flow
------------------------------	---------------------------------



<b>Storage Temperature</b>	-40°C ~ 75°C (-40°F ~ 167°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing

<b>Weight</b>	0.44lbs (0.2kg)
<b>Power Requirement</b>	DC in +9V ~ +36V
<b>ACPI</b>	Single power ATX Support S0,S3, S4, S5 ACPI 5.0 Compliant
<b>Power Mode</b>	AT/ATX (Default Setting: AT)
<b>Dimension (L x W)</b>	5.7" x 4" (146mm x 101mm)
<b>Software Support</b>	
<b>OS Information</b>	Win 10 Linux
<b>Ordering Information</b>	
<b>Ordering Information</b>	ECM-EHL3-J6412-A1R ECM-EHL3/J6412/1SATA/6COM/8USB/3LAN/A1  ECM-EHL3-J6413-A1R ECM-EHL3/J6413/1SATA/6COM/8USB/3LAN/A1  ECM-EHL3-X13E-A1R ECM-EHL3/X6413E/1SATA/6COM/8USB/3LAN/A1  ECM-EHL-X25RE-A1R ECM-EHL3/X6425RE/1SATA/6COM/8USB/3LAN/A1