




## ECM-APL2-A

Intel® Apollo Lake 3.5" Micro Module



- > Bottom Layer Soldered
- > Intel® Pentium®/Celeron®/Atom™ BGA Processor
- > Intel® HD Graphics 500/505
- > Single DRAM Socket, Max. Up to 8GB DDR3L 1600&1333MHz
- > Triple Display (Dual HDMI, VGA)
- > Dual Expansion Slot, 2-mCPle
- > Dual Gigabit Ethernet, HD Audio Code
- > TPM 2.0

### + Spec

-System Information-	
<b>Processor</b>	Intel® Celeron® Processor J3455 (2M Cache, up to 2.30 GHz)
<b>System Memory</b>	1 x 204-Pin SO-DIMM Socket, Max. Up to 8GB DDR3L 1600&1333MT/s
<b>I/O Chipset</b>	EC IT8528E/ IT8528I
<b>BIOS Information</b>	AMI uEFI BIOS, 128Mbit SPI Flash ROM
<b>Watchdog Timer</b>	H/W Reset, 1sec. ~ 65535sec. and 1sec./step
<b>H/W Status Monitor</b>	Monitoring System Temperature, Voltage and FAN Status with Auto Throttling Control
Expansion	
<b>Expansion</b>	1 x Full Size mPCle 1 x Half Size mPCle
Storage	
<b>Storage</b>	1 x mSATA (Shared mCPle)
I/O	
<b>USB Port</b>	4 x USB 3.0 2 x USB 2.0
<b>COM Port</b>	2 x RS-232/422/485
<b>SATA</b>	1 x SATA III
<b>DIO</b>	1 x 8bit GPIO
<b>MIO</b>	1 x LPC 1 x SPI
Display	
<b>Graphic Chipset</b>	Intel® HD Graphics 500 (E3930, E3940, J3455, N3350) Intel® HD Graphics 505 (E3950, N4200)
<b>Spec. &amp; Resolution</b>	2 x HDMI 1.4: Max. Resolution 3840x2160 @ 30Hz 1 x VGA: Max. Resolution 1920x1200 @ 60Hz
<b>Multiple Display</b>	Triple Display
Audio	
<b>Audio Codec</b>	Realtek ALC888S, supports 5.1-CH
<b>Audio Interface</b>	1 x Mic-In 1 x Line-In 1 x Line-Out
Certifications	
<b>Certification Information</b>	CE FCC Class B
Ethernet	
<b>LAN Chipset</b>	2 x Intel® I210AT
<b>Ethernet Interface</b>	10/100/1000 Base-Tx GbE compatible
<b>LAN Port</b>	2 x RJ45 with ACT/LINK and SPEED LEDs
Mechanical & Environmental	
<b>Operating Temperature</b>	0°C ~ 60°C (32°F ~ 140°F), with 0.2m/s air flow
<b>Storage Temperature</b>	-40°C ~ 75°C (-40°F ~ 167°F)
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Weight</b>	0.44lbs (0.2kg)
<b>Power Requirement</b>	DC in +12V ~ +24V
<b>Power Mode</b>	AT/ATX
<b>Dimension (L x W)</b>	5.7" x 4" (146mm x 101mm)
Software Support	



<b>OS Information</b>	Win 10 Linux
<b>Ordering Information</b>	
<b>Ordering Information</b>	ECM-APL2-J3455-C3R 3.5" W/J3455/6USB/2COM/2LAN/C3  ACC-ECMAPL2-SD-2R Heat spreader for ECM-APL2 NJ series