



Rating:
 10A 250V AC UL cUL
 10A 250V AC VDE 3C KC
Fuse: 250V AC 6.3A 2.5W
Insert And Extract Force: 1.36kgf~6.8kgf
Terminal Strength: ≥60N
Operating Life: ≥6000 cycles
Withstand Voltage: Between all terminals:2500VAC(50-60Hz)1m
 Terminals to Base:3750V AC(50-60Hz)1min
Leakage Current: 1mA
Insulation Resistance: ≥100MΩ 500V DC
Body Materil: NYLON 94V-2~0

| | | | | | | | | | | | | | |
|------|------|----------------------|-------|--------------------|-------|-----------|------------|-------------|-----|--------------|----------------|-------|---------|
| A4 | | | | 普通公差: | | CONNTHERM | | | | | | | |
| A3 | | | | COMMON TOLERANCE : | | | | | | | | | |
| A2 | | | | UP TO 5 | ±0.20 | 单位 | mm | 投影 | ☐ ⊕ | 品名 | Ac Inlet C14型 | 比例 | Free |
| A1 | | | | ABOVE 5 TO 30 | ±0.30 | UNIT | | PROJECTED | | PRODUCT NAME | | SCALE | 版本号 |
| REV. | DATE | REVISION DESCRIPTION | ISSUE | ABOVE 30 | ±0.50 | 绘图 | 金泽杰 | 核对 | 张卓龙 | 型号 | | | VERSION |
| | | | | ANGULAR | ±5° | 日期 | 2023. 8. 3 | 核准 | 王天建 | 料号 | AAC-111-6.3-LC | | |
| | | | | | | DATE | | APPROVAL BY | | PART NO. | | | |