



## VNS-10WR2

### 10.1" ultra slim Panel PC

- > RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
- > 2GB / 4GB RAM
- > 32GB eMMC
- > PCAP Touch
- > 10/100/1000 Ethernet
- > Touch button (Power/ Brightness/ Volume/ LED)
- > RS232, RS422 or RS485
- > DC 12~24V Input or Powered LAN 802.3at
- > NFC Reader
- > D-MIC
- > 2.0MP Camera
- > Speak 4Ω 2.0W
- > LED Indicating Light Bar
- > 75 x 75mm VESA Mount
- > Plastic has Antibacterial

#### + Spec

-System Information-	
<b>Processor</b>	RockChip RK3568 Cortex-A55, Quad Core up to 2.0GHz
<b>System Memory</b>	2GB / 4GB DDR4 RAM
Storage	
<b>Storage</b>	32GB eMMC
Panel	
<b>LCD Size</b>	10.1"
<b>Resolution</b>	1280x800
<b>Luminance</b>	350
<b>Viewing angle</b>	170° (H/V)
<b>Touch Type</b>	PCAP
I/O	
<b>USB Port</b>	2 x USB 2.0
<b>External I/O Connector</b>	1 x RJ45 for RS232, RS422 or RS485 2 x USB 2.0 Type A 1 x 10/100/1000 Ethernet 1 x 4-Pin 3.5mm Audio Jack
<b>Camera</b>	2.0MP Camera
System Control	
<b>LED Indicator</b>	Light color: 24-bit / true color Illuminating area: 70*8mm(front),70*5mm(side)
Data Collection	
<b>Camera</b>	2M pixel
<b>NFC</b>	NFC Reader
Wireless Communication	
<b>WLAN</b>	802.11 b/g/n
Display	
<b>Spec. &amp; Resolution</b>	LVDS: Max. resolution 1280x800 @ 60Hz
Audio	
<b>Speaker Output</b>	4Ω 2.0W/2.2W(MAX)
Certifications	
<b>Certification Information</b>	CE, FCC Class B
Ethernet	
<b>LAN Chipset</b>	Realtek RTL8211F-CG
<b>LAN Port</b>	1 x RJ45
Power Requirement	
<b>Adapter</b>	Input: 100~240 Vac/50~60 Hz Output: 60W Adapter (12V @ 5A Adapter)
Mechanical & Environmental	
<b>Operating Temperature</b>	0°C ~ 40°C
<b>Storage Temperature</b>	-10°C ~ 60°C
<b>Operating Humidity</b>	40°C @ 95% Relative Humidity, Non-condensing
<b>Weight</b>	1.1 kg
<b>VESA</b>	75 x 75
<b>Power Requirement</b>	DC Input, 12~24V
<b>Power Mode</b>	DC jack or Powered LAN 802.3at
<b>Dimension (L x W)</b>	270 x 193 x 28 mm
Software Support	
<b>OS Information</b>	Android 11, Debain 11