


RoHS Compliance



Nut

Washer

Electrical Specifications:

Rating: 3A 125V AC, 1A 250V AC

Contact Resistance: 20mΩ Max

Insulation Resistance: 100MΩ/500VDC Min

Withstanding Voltage: AC1000V/1Min

Operating Temperature: -25°C ~ +85°C

Electrical Life: 50000 Cycles

Button Color: Red

Packing: 100PCS/Bag

500PCS/Bag

2000PCS/CTN(Nut & Washer)

Note

1: Open/Short Text 100% Text. insulation: Min, 2M

2: All must be meet on RoHS Compliant

| ITEM | PART NAME | Description | UNIT | Q'TY |
|------|------------------|---|------|------|
| 5 | Heat Shrink Tube | φ3.0x10mm Heat Shrink Tube,Black | PCS | 2 |
| 4 | Cable | UL2468-22AWG Red/Black,OD 3.4x1.5mm,L398mm | PCS | 1 |
| 3 | Washer | φ10x7.2x1.0mm Spring Washer,Iron,Nickel Plated | PCS | 1 |
| 2 | Nut | M7x0.75mm Nut, HEX=10.0mm,T=1.9mm ,Iron,Nickel Plated | PCS | 1 |
| 1 | Push Switch | M7x0.75mm Push Switch, Push OFF,3A 125VAC, Red Knob | PCS | 1 |

| ANGLE TOLERANCE | PROJECTION | Description: |
|-----------------|------------|--|
| ±3° | | Momentary Pushbutton Switch with Calbe |

| GENERAL TOLERANCE | UNITS | mm | P/N: |
|-------------------|------------|--------|------------|
| x.x ±0.30 | SHEET SIZE | A4 | Rev. 3.0 |
| x.xx ±0.20 | Draw: | Daniel | 2024-05-17 |
| x.xxx ±0.10 | Check: | Daniel | 2024-05-17 |

SW-PBS-004C-R-L40

CONNTERM

1 2 3 4 5 6 7 8