

OSM-3568

Open Standard Module-Computer on
Module with Rockchip RK3568J Quad-core
Cortex-A55



Product Features

- OSM 1.1 size-L type 45*45mm
- 2GB LPDDR4
- OS supports Debian 11, Android 11
- Enhanced reliability for mobile edge devices
- 16GB eMMC
- Wide operating temperature: -40~85°C

Specification

System Information

System Memory	2GB LPDDR4
Processor	Quad-core Cortex-A55
Chipset	Rockchip RK3568J

Storage

Storage	16GB eMMC 5.1
---------	---------------

OSM Module I/O

PCIe	1 x 3.0 1 x 2.0
GPIO	x 24
LVDS	x 1 single channel (share with MIPI DSI)
HDMI	x 1, 4k60Hz
I2C	x 3
eDP	x 1
MIPI CSI	x 1 (4 lane)

MIPI DSI	x 2 (4 lane) one share with LVDS
----------	----------------------------------

SPDIF	x 1
-------	-----

I2S	x 2
-----	-----

SPI	x 2
-----	-----

CAN	x 2
-----	-----

SDIO	2 x SDIO 3.0
------	--------------

COM	1 x debugging port 2 x UART
-----	--------------------------------

Network	2 x RJ45, 1000M
---------	-----------------

USB Port	1 x USB Host 3.0 1 x USB OTG 3.0 2 x USB Host 2.0
----------	---

Certifications

Certification Information	CE, FCC Class B
---------------------------	-----------------

Mechanical & Environmental

Storage Temperature	-40~95 Degree
---------------------	---------------

Dimension	45mm x 45mm (Size-L)
-----------	----------------------

Power Requirement	DC input voltage 5V
-------------------	---------------------

Operating Humidity	5% to 95%, non-condensing
--------------------	---------------------------

Operating Temperature	Industry: -40~85 Degree
-----------------------	-------------------------

Software Support

OS Information	Linux Debian 11 (First), Android 11
----------------	--

Ordering Information

Ordering Information	TBD
----------------------	-----

Development board Interfaces

Gigabit Ethernet	RJ45 (100M/1000M Ethernet)x2
------------------	------------------------------

USB	2 x USB 3.0 Host, 2 x USB 2.0 Host, 1 x USB Type C(OTG)
-----	---

Mini-PCIE	x 1
-----------	-----

MIPI CSI	x 1
----------	-----

MIPI DSI	x 1
----------	-----

DC-IN	x 1
SW	K1 (Recovery mode)
Dimensions	125 x 120 mm
Display	Support HDMI x 1 /eDP x 1, MIPI DSI interface
CAN	x 2
SPI	x 1
UART	x 2
Adapter	DC input voltage 12V
