



■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 7A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 40°C to + 105°C
- Contact Resistance : 20mΩ max

■ WAFER

- Part No. : JS-1150-XX (Straight)
- Poles : 2-24
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-2
- Q' ty : 1000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-1150- 2	-----	5.60
4	JS-1150- 4	4.20	9.80
6	JS-1150- 6	8.40	14.00
8	JS-1150- 8	12.60	18.20
10	JS-1150-10	16.80	22.40
12	JS-1150-12	21.00	26.60
14	JS-1150-14	25.20	30.80
16	JS-1150-16	29.40	35.00
18	JS-1150-18	33.60	39.20
20	JS-1150-20	37.80	43.40
22	JS-1150-22	42.00	47.60
24	JS-1150-24	46.20	51.80



喬訊電子工業股份有限公司

CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

PART NO | JS-1150-XX
4.20mm Mini-Fit D/R Power Connectors Wafer

APPROVED BY	SCALE	UNIT	TOLERANCE		LTR	REVISION RECORD	DATE
	2:1	mm	.0	±0.3			
CHECKED BY	PROJ	VER NO.	.00	±0.2			
			.000	±0.1			
DRAWN BY	DATE	SIZE	ANGLE				
	2004/04/20	A4	0°	±			
			.0°	±			