


Recommended P.C. Board Layout

Material:  
 \* Insulation: Nylon 66, Color Nature  
 \* Contact: Brass  
 Circuit Pattern Schedule: See Drawing No: CP0110S\*

Ordering Code:



- ① Series No.
- ② Type of Connector:  
3= Straight PCB mount header
- ③ No of Circuits:
- △④ Plating Code:  
1= 2.54μm(100μ") Tin over 1.02μm(40μ") Nickel  
2= Gold flash plated over 0.76μm(30μ") Nickel  
B= Selective 0.38μm(15μ") gold plated over 1.27μm(50μ") Nickel  
C= Selective 0.76μm(30μ") gold plated over 1.27μm(50μ") Nickel
- ⑤ Variation:  
1= UL 94V-2, Without mounting pegs  
3= UL 94V-0, Without mounting pegs
- ⑥ Option: 0= Standard

④					DATE	UNIT: mm / inch	TITLE: STRAIGHT HEADER	瀚荃股份有限公司 CviLux Corporation			
③					DRAWN BY: Casey	01/28-04'	CP-01 POWER CONNECTOR				
②					ENGINEER: Eisley	02/02-04'	MATERIAL:	DRAWING NO. CP0128SJ	PART NO.	CP-013***10	
①	SUN	1/15/04'	ECN04025		CHECKED BY: David	02/03-04'	FINISH:	SCALE 2 / 1	SHEET 1	OF 1	
SYM	NAME	DATE	REVISIONS		APPROVED BY: Alex	02/03-04'					