

**Polymer
PTC Devices**

Surface mount fuses

Shanghai Wayon Thermo/Electro Materials Co.,Ltd.
10th Floor, No.201, New Jinqiao Road, Shanghai 201206,China
Tel: 86-21- 50320161 58995165 Fax: 86-21-50320266
E-mail: market@way-on.com [Http://www.way-on.com](http://www.way-on.com)



LP-ISM010


Features

- Small size of 0805
- Lead-free and compliant with the European Union RoHS Directive 2002/95/EC
- Fast tripping resettable circuit protection
- Surface mount packaging for automated assembly
- Agency Recognition: UL pending



Product Dimensions (mm)

Part number	A Max.	B Max.	C Max.	D Min.	E Min.	Part marking
LP-ISM010	2.20	1.50	1.00	0.10	0.20	0




Electrical Characteristics

Part number	I _H (A)	I _T (A)	V _{max} (V)	I _{max} (A)	T _{trip} Current(A) Time(S)	P _{d typ} (W)	R _{min} (Ω)	R _{1max} (Ω)
LP-ISM010	0.10	0.30	15.0	10.0	0.50 1.50	0.5	1.00	6.00

I_H=Hold current: maximum current at which the device will not trip at 25°C still air.
I_T=Trip current: minimum current at which the device will always trip at 25°C still air.
V_{max}=Maximum voltage device can withstand without damage at rated current.
I_{max}=Maximum fault current device can withstand without damage at rated voltage.
T_{trip}=Maximum time to trip(s) at assigned current.
P_{d typ}=Typical power dissipation: typical amount of power dissipated by the device when in state air environment.
R_{min}=Minimum device resistance at 25°C prior to tripping.
R_{1max}=Maximum device resistance measured in the nontripped state 1 hour post reflow.

Solder Reflow Recommendations



Solder Pad Layouts

Part number	A (mm)	B (mm)	C (mm)
LP-ISM010	1.20	1.00	1.50

- * Recommended reflow methods: IR, Vapor phase, hot air oven.
- * Devices can be cleaned using standard industry methods and solvents.

Notes:

- If reflow temperatures exceed the recommended profile, devices may not meet the performance requirements.
- Devices are not designed to be wave soldered to the bottom side of the board.

Package Information

Tape & Reel: 5000pcs per reel.

Effectivity: Reference documents shall be the issue in effect on the date of invitation for bid.

Caution: Operation beyond the rated voltage or current may result in rupture electrical arcing or flame.

