



Features

- Supports VGA / YPbPr & DVI Input
- Supports 5-wire USB Touch
- Non-Touch Available
- 2W Amplifier Audio Output
- +12 V Input
- 100 x 100 VESA Standard



Specifications

Panel	
• LCD Size	15", 4:3
• Display Type	XGA TFT
• Resolution	1024 x 768
• Color	16.7M
• Pixel Pitch	0.297mm(H) x 0.297mm(V)
• Luminance	250 cd/m2
• Contrast Ratio	500
• Viewing Angle	65(U), 60(D), 70(L), 70(R)
• Response Time	8 ms
• Back Light	2 x CCFL
• Touch Screen	5-wire Resistive
• Light Transmission	80%
• Touch Interface	USB
System	
• Board	EPM-1525
Rear I/O	
• VGA / YPbPr	1 x DB-15
• DVI	1 x DVI
• Audio port	1 x Line in
• USB	1 x USB 2.0 for touch
• Speaker	2 x 2W

Environment & Mechanical	
• Color	Front & Rear panel Black (Plastics)
• Mounting	Wall Mount/Stand/VESA 100 X 100 mm
• Power Input	100~250 Vdc / 47~63 Hz
• Power Output	+12 Vdc / 5 A (60W)
• Operating Temperature	0~40°C (32~140°F)
• Storage Temperature	-10°C~50°C
• Relative Humidity	0%~90% relative humidity, non-condensing
• Dimension (W x D x H)	340 x 285 x 53 mm
• Weight	2.79 Kgs

Ordering Information

- **PPC-1500**
15" XGA TFT Touch Monitor
- **ACC-ARM-D1R**
VESA STAND, 75 & 100mm