



■ SPECIFICATIONS

- Voltage Rating : 300-600V AC/DC
- Current Rating : 9-15A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M Ω min.
- Temperature Range : - 25 $^{\circ}$ C to + 85 $^{\circ}$ C
- Contact Resistance : 20m Ω max.

■ TERMINAL

- ⚠ Part No. : JS-2000W-TX
Code No. ①
- ① Applicable Wires : TH : AWG# 14 - 18
TL : AWG# 18 - 22
- Material : Brass
- Finish : Tin Plated
- Thickness : 0.25mm
- Q' ty : JS-2000W-TH : 3,500 pcs./Reel
JS-2000W-TL : 5,000 pcs./Reel

Part No.	Dimensions(mm) ± 0.4			
	A	B	C	D
JS-2000W-TH	4.80	4.50	3.00	3.80
JS-2000W-TL	4.10	3.30	2.50	2.20



喬訊電子工業股份有限公司
CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

PART NO JS-2000W-TX

∅2.00mm Power Connectors Terminal

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
張育瑞		mm	.0 ±0.30	⚠	刪除GP編碼	吳弘文	2004/12/31	⚠			
CHECKED BY	PROJ	VER NO.	.00 ±0.20	⚠				⚠			
黃科源	⊕	a1	.000 ±0.10	⚠				⚠			
DRAWN BY	DATE	SIZE	ANGLE	⚠					CUSTOMER		
吳弘文	2013/05/30	A4	0° ±1°	⚠					Conforms to The RoHS Instruction		
			.0° ±	⚠							
			SHEET 1/1	⚠							