

POSITION	A	B
6	11.2	4.0
8	13.2	6.0
10	15.2	8.0
12	17.2	10.0
14	19.2	12.0
16	21.2	14.0
18	23.2	16.0
20	25.2	18.0
22	27.2	20.0
24	29.2	22.0
26	31.2	24.0
30	35.2	28.0
32	37.2	30.0
34	39.2	32.0
36	41.2	34.0
38	43.2	36.0
40	45.2	38.0
44	49.2	42.0
48	53.2	46.0
50	55.2	48.0
56	61.2	54.0
60	65.2	58.0
64	69.2	62.0
68	73.2	66.0

**SPECIFICATIONS**

**Material**

Insulator : PBT, glass reinforced, rated UL 94V-0

Contact : Phosphor Bronze

**Electrical**

Current Rating : 1 Amp

Contact Resistance : 30 mΩ max.



Insulation Resistance : 3000 MΩ min.

Dielectric Withstanding Voltage : 500V AC for 1minute

Operating Temperature : -40°C to +105°C

◆ Terminated with L02-1.00mm pitch flat ribbon cable.

◆ Mating Suggestion : C05a, C05d, C05e, C05j, C06a & C06s series.

UNLESS OTHERWISE SPECIFIED TOLERANCE .X ±0.3 .XX ±0.2 .XXX ±0.1		 <b>DON CONNEX ELE. CO., LTD</b>
UNIT: mm		
SCALE: /	SHEET:1/1	DRAW NO. A05-01CAT-A
THIRD 		FILE NO. A05-01CAT-A
RD	CHECK	2009/05/18