



■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 7A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 40°C to + 105°C
- Contact Resistance : 20mΩ max

■ WAFER

- Part No. : JS-1151-XX (Straight)
- Poles : 2-24
- Material : Contact : Brass, Tin Plated
Base : Nylon 66 UL94V-2
- Q' ty : 1000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-1151- 2	-----	5.60
4	JS-1151- 4	4.20	9.80
6	JS-1151- 6	8.40	14.00
8	JS-1151- 8	12.60	18.20
10	JS-1151-10	16.80	22.40
12	JS-1151-12	21.00	26.60
14	JS-1151-14	25.20	30.80
16	JS-1151-16	29.40	35.00
18	JS-1151-18	33.60	39.20
20	JS-1151-20	37.80	43.40
22	JS-1151-22	42.00	47.60
24	JS-1151-24	46.20	51.80



喬訊電子工業股份有限公司

CHYAO SHIUNN
ELECTRONIC INDUSTRIAL LTD.

APPROVED BY

SCALE

UNIT

TOLERANCE

LTR

REVISION RECORD

DATE

CHECKED BY

PROJ

VER NO.

.0 ±0.3

ECR

200404-016

2004/04/20

DRAWN BY

DATE

SIZE

.00 ±0.2

.000 ±0.1

ALL ±

ANGLE

0° ±

.0° ±

PART NO JS-1151-XX

4.20mm Mini-Fit D/R Power Connectors Wafer

2004/04/20

A4