

# Rextorm

## PX - 501

10.1" Full Rugged Windows Pad


Extreme Power  
with  
Extensibility



- ◆ 4th generation Intel® Core™ i5 processor 4300U vPro™ 1.9GHz
- ◆ IP65, MIL-STD-810G, 5 feet drop resistance
- ◆ 1000 nit sunlight readable display
- ◆ Capacitive multi-touch supports glove touch, water rejection, palm rejection, 2mm hard tip stylus and digitizer
- ◆ GNSS, Wi-Fi, Bluetooth, optional 4G LTE
- ◆ Hot swappable battery design
- ◆ Wide expansion design for data capture
- ◆ Dual pass-through connector for WLAN, GNSS, WWAN

### I/O Diagram

### I/O Diagram



# Specifications

## Operating System

- Windows Embedded 8.1 Industry 64-bit
- Windows Embedded Standard 8 64-bit
- Windows 7 Professional 64-bit
- Windows Embedded Standard 7 64-bit

## CPU

- 4th generation Intel® Core™ i5 processor 4300U vPro™ 1.9GHz

\* vPro™ by request

## Memory

- 4GB DDR3L (8GB by request)

## Storage

- 120GB mSATA SSD (option 240GB)

## Display

- 10.1-inch 1920 x 1200 WUXGA; 1000 nit sunlight readable
- 10-point capacitive touch supports glove touch, water rejection, palm rejection, 2mm hard tip stylus
- Gorilla Glass3
- Digitizer

## RF

- Wi-Fi 802.11 a/b/g/n/ac
- Bluetooth V4.0
- Optional 3.5G or 4G LTE
- GNSS(GPS/Glonass/BeiDou)

## Webcam

- 2MP front camera
- 5MP rear camera with auto focus and LED flash

## Data Collection

- Magnetic stripe reader (snap-on, by request)
- Smart card reader-CAC (snap-on, by request)
- NFC (snap-on, by request)
- 2D barcode reader (option)

## Control Button

- Programmable button x 3
- Barcode trigger x 1
- Power, volume, Windows button

## LED Indicator

- Power on/off
- Wi-Fi on/off
- Fn on/off
- Battery full/charging/low

## Sensor

- Gyroscope, G-sensor, E-compass, light sensor

## Power Adapter

- AC 100V~240V, 50~60Hz Input; 19VDC@3.42A, 65W

## Battery

- Standard : 4500mAh, 10.8V, hot swappable battery  
Battery operation\* : 6 hours
- Extended : 9000mAh, 10.8V, hot swappable battery (option)  
Battery operation\* : 11 hours

\*The listed battery life is based on MobileMark 2012<sup>®</sup> media mode testing.

## I/O Interface

- USB 3.0 type A x 1
- Gigabit ethernet (RJ-45 ) x 1
- RS-232 (optional for USB 2.0 type)
- Audio jack (headphone/microphone combo) x 1
- RF pass-through connector x 2 for WLAN,GNSS, WWAN
- 12-pin docking connector x 1
- Micro SD slot x 1, Micro SIMslot x 1, Micro HDMI x 1
- Speaker & microphone

## Dimensions and Weight

- 28 x 19.5 x 2.3 cm (11" x 7.7" x 0.9")
- 1.36 kg (3.0 lbs)

## Rugged Features

- IP65, MIL-STD-810G, shock & vibration, 5 feet drop

## Environment

- Operating temperature -20°C to 60°C
- Storage temperature -30°C to +70°C
- Humidity 5%~95%

## Software

- DsahON\* \*available to download from RuggON website

## Security

- TPM 1.2

## In-box Accessory

- Digitizer pen
- Hand strap
- Shoulder strap
- Handle
- Power adapter



www.ruggon.com

e-Mail: info@ruggon.com