
IFO2225-830-FL

22" TFT Fanless Touch Panel Computer with Intel® Atom™ Processor N270



Introduction

The IFO2225-830-FL is a slim panel computer equipped with a 22-inch 300 nits WSXGA+ LCD display that supports an superior Intel[®] Atom[™] processor N270. Powered by an Intel[®] 945GSE+ICH7M core logic chipset with maximum 256MB sharing graphics memory, this panel computer has enhanced graphics performance. The panel also supports DualView and multiple I/O options including 4 USB 2.0 and 4 RS-232 ports. The IFO2225-830-FL supports an antenna for 802.11b/g wireless connection. The Gigabit Ethernet ports provide an extremely high speed of Ethernet connectivity. It features low noise, low power consumption, high reliability and high performance. Its excellent industrial

design (ID) and user friendly interface design makes the IFO2225-830-FL a safe, reliable & user-friendly panel computer. Best suited for infotainment, media content display and DSA solutions.

Water/dust-proof design for entire system: IPX1

The IPX1-rated water/dust-proof housing protects the entire system from outside damage of water drip in a public place. Its unique design improves system stability and saves maintenance/re-installation time.

Specifications

Front Bezel	Plastic ABS (Black)		BIOS	AMI BIOS with SmartView and Customer
LCD Panel	Display Type	22" WSXGA+ TFT		CMOS Backup
	Brightness (cd/m ²)	300 nits	Storage	Supports 1 x 2.5" SATA HDD
	Resolution	1680 x 1050		1 x CompactFlash™
	Viewing Angle (H/V)	178°/178°	Optical Drive	1 x combo drive (optional)
Main System	CPU	Intel [®] Atom [™] processor N270 1.6 GHz	Watchdog	255 levels, 1~255 sec.
	Chipset	Intel [®] 945GSE + ICH7M	Timer	
	System Memory	1 x DDR2 SO-DIMM max. up to 2 GB	Onboard	Integrated in Intel® 945GSE; max. memo
			Graphics	shared 256 MB

I/O Connectors	3 x RS-232 (COM 2/3/4)	
	1 x RS-232/422/485 (COM 1)	
	4 x USB 2.0	
	1 x Audio (Line-out)	
	1 x VGA	
	1 x 10/100/1000Mbps Ethernet	
Expansion Interface	1 x Mini card slot	
Camera	1 x 1.3 mega pixels camera	
Touchscreen	Resistive type	
Power Supply	24V _{DC} with AC-DC power adaptor	
Dimensions	573.5 mm (22.58") (W) x 68.5 mm (2.69") (D)	
	x 399 mm (15.71") (H)	
Weight (net/gross)	8.22 kg (18.12 lb)/9.87 kg (21.76 lb)	
Environment	Operating temperature: $0^{\circ}C \sim +40^{\circ}C (32^{\circ}F \sim 104^{\circ}F)$	
	Relative humidity: 10% ~ 95%, non-condensing	
	Shock: 10G peak acceleration (11 sec. duration)	
Certification	CE	

Ordering Information

IF02225-830-FL-AC-CO	22" TFT high brightness fanless panel computer with Intel [®] Atom™ N270, resistive T/S, combo and camera
IFO2225-830-FL-AC	22" TFT high brightness fanless panel computer with Intel [®] Atom™ N270, resistive T/S (w/o combo and camera)

* Specification and certifications are based on options and may vary.

Optional Accessories

E202003330	VM-101 VESA ARM (clamp type)	
E202003329	VM-105 VESA ARM (wall mount type)	
E222175103	22" stand kit	

Optional EOS Installation

Windows[®] XP Embedded

Optional OS Installation

Windows[®] XP Windows[®] 7 Overview

Digital Signage

Healthcare & Medical Solutions > Medical Panel

Healthcare & Medical Solutions > Medical Grade

Fanless & Heavy-duty Touch Panel Computers

Touch Panel Computers for Infotainment

Industrial Touch Pa Computers & Monit > Industrial Touch Panel Computer

Industrial Touch Pane Computers & Monito > Industrial Touch Panel Monitors

Open Frame Pane Computers

Accessories

Dimensions

