

SPECIFICATION FOR APPROVAL

CUSTOMER:	MARITEX	CUST.P/N:	
ORDERING CODE:	K5B T 3.5x3x0.8-T52	K.C.P/N:	PX0306IT
(1) SHAPE :		A	3.50±0.15 mm
		B	3.0±0.2 mm
		C	52.4±1.5 mm
		D	mm
		E	5.0±0.5 mm
		F	mm
		G	mm
		G	mm
(2) ELECTRICAL REQUIREMENTS:		(3) TEST CONDITIONS:	
$Z_1 = 33 \text{ min OHM AT } 25 \text{ MHz}$ $Z_2 = 60 \text{ min OHM AT } 100 \text{ MHz}$		1 IMPEDANCE ANALYZER: HP4191A TEST FIXTURE: HP16092A 2. WIRE: $\Phi 0.65$ T.C. Wx63mm x 1/2Ts 3. DRAWING:	
(4) PACKING <input type="checkbox"/> IN BULK <input type="checkbox"/> VACUUM <input type="checkbox"/> INSERTION PCS/BAG* BAGS/INNER BOX BOXES/CARTON = PCS PCS/PLATE* PLATES/CARTON= PCS PCS/TRAY* TRAYS/CARTON= PCS 5000 PCS/REEL 5 REELS/CARTON= 25000 PCS		(5) APPEARANCE Area of break $\leq 1/3$ terminal area	
		Depth of break $\leq 1/2$ wall thickness	
(6) REMARK:		Approved by 吴炳勋	
		Checked by 吴明珠	
		Drawn by 鍾佩宜 2011-06-24	
		DWG.NO. 20116057A	

TEST DATA FOR PREPRODUCTION SAMPLES

CUSTOMER	MARITEX			CUST. P/N		
ORDERING CODE	<i>K5B T 3.5x3x0.8-T52</i>			K.C. P/N	<i>PX0306IT</i>	
TEMP.	24 °C	RH	69 %	DWG.NO.	20116057A	
WIRE	0.65x63mm T.C.W	WINDING	1/2 Ts	Q'TY	5PCS	
Test Instruments						
Meas. Item.	Z (OHM)	Z (OHM)	A mm	B mm		
Specification	20 min	30 min	3.50±0.15	3.0±0.2		
Test Freq.	25 MHz	100 MHz				
sample#1	34	61	3,44	2,96		
sample#2	33	57	3,46	2,99		
sample#3	33	59	3,49	2,97		
sample#4	34	59	3,44	2,94		
sample#5	34	60	3,47	2,98		
sample#6						
sample#7						
sample#8						
sample#9						
sample#10						
— X	33,6	59,2	3,460	2,968		
R	1	4	0,05	0,05		
REMARK:				Approved by: 吳炳勳		
				Checked by: 吳明珠		
				Drawn by: 鍾佩宜		