



- NOTES:
1. Rating: 300V/16A
<IEC> 320V/20A
 2. Poles: 02-24P
 3. Insulation Withstands Voltage: AC2000V/1 Min
 4. Contact resistance: 20m Ω
 5. Insulation Resistance: 500M Ω at DC500V
 6. Using Temperature Range: -40°C/+115°C
 7. Max soldering : +250° for 5S
 8. RoHS Compliance:
 9. With" \star "is import dimension

How to order
U10-TB27 - 2RC /5.08 - XX P -Y 0 0 0A

Certificate Series NO. Factory Code poles color: Customer requirements

- 1: Grey
- 2: Blue
- 3: Black
- 4: Green
- 5: Orange
- 6: Red
- 7: transparent
- 8: Yellow
- 9: White

Total Pitch Tolerances		Nominal dimension range	
In mm		In mm	
over	0	over	0
to	30	to	30
53	to	53	to
70	to	70	to
90	to	90	to
115	to	115	to
150	to	150	to
200	to	200	to
250	to	250	to
30	to	30	to
53	to	53	to
70	to	70	to
90	to	90	to
115	to	115	to
150	to	150	to
200	to	200	to
250	to	250	to
320	to	320	to
10	to	10	to
30	to	30	to
53	to	53	to
70	to	70	to
90	to	90	to
115	to	115	to
150	to	150	to
200	to	200	to
250	to	250	to
320	to	320	to
0.2	to	0.2	to
0.3	to	0.3	to
0.3	to	0.3	to
0.2	to	0.2	to
0.3	to	0.3	to
0.5	to	0.5	to

2	Solder Pin	3140000018/19	2	Brass	Sn Plated
1	Housing	4030001479	1	PA66	UL94V-0
ITEM	NAME OF PART	NO OF PART	Q'TY	MATERIAL	NOTE
DWG	DATE	18.10.17	UNITS	MM	SHEET/OF 1/1
CHK	DATE		SCALE	1:1	A4
APP	DATE		NAME	U10-TB27-2RC/5.08-XXP-Y000A	
NINGBO ULO ELECTRONICS CO.,LTD.			DWGNO.	UL01B27Y001A	