



LPC-1531

15" Intel® Celeron® SoC N3000 family Processor
Fanless Rugged Touch Panel PC

- > Onboard Intel® Celeron® SoC N3000 family BGA Processor
- > One 204-pin DDR3L SODIMM Socket Supports Up to 8GB DDR3L 1600 SDRAM
- > 4 USB, 2 COM
- > Dual RealTek RTL8119 Gigabit LAN
- > Wide Voltage +12V ~ +26V Input, ErP Power
- > Backlight Controlled by PWM
- > IP65 Compliant Front Panel
- > Timer-Power-On
- > TPM 1.2 Function (Optional)

+ Spec

System	
Processor	Intel® Pentium®/Celeron® processor
System Memory	1 x 204-Pin DDR3L 1600MHz SO-DIMM up to 8 GB
I/O Chip	Nuvoton NPCE388N
Watchdog Timer	H/W Reset, 1sec. ~ 65535sec./1sec.step
H/W Status Monitor	Monitoring SYSTEM Temperature and Voltage with Auto Throttling Control
Expansion	
Expansion	1 x Mini PCIe Support mSATA 1 x Mini PCIe Supports SIM Card
Storage	
Storage	1 x 2.5" Drive Bay 1 x Onboard eMMC (32G reserved)
I/O	
USB	4 x USB 3.0
SATA	1 x SATA III
COM Port	2 x RS-232/422/485 (Factory Optional)
Other	1 x HDMI 1 x Knockouts for Antenna Mounting
Display	
Chipset	Intel® Braswell SoC integrated Graphics Supports dual display
Resolution	HDMI:Max. resolution 1920x1200 @ 60Hz
Audio	
Chipset	Realtek ALC233 supports 2.1-CH
Audio Interface	Line-Out
Speaker Output	2 x 1W
Ethernet	
Chipset	2 x Realtek RTL8119
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
LAN Port	2 x RJ-45
Mechanical & Environmental	
Power Type	AT/ATX (ATX is default setting)
Operating Temp	-10°C ~ 50°C
Storage Temp	-20°C ~ 60°C
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Weight	2.84 Kgs
Mounting Kit	Wall / Stand / VESA 75mm x 75mm
Dimension (L x W x H)	283 x 222 x 45 mm
Vibration Test	With SSD/mSATA : 1.5Grms, IEC 60068-2-64, Random, 5 ~ 500Hz, 30min/axis
Shock Test	With CF/SSD : 10Grms, IEC 60068-2-27, Half Sine, 11ms
System Fan	Fanless
Construction - Front	Silver Aluminum
Construction - Rear	Black
Certifications	
Certification Information	CE FCC Class B
Software Support	
OS Information	Win 7 Win 8 Linux
Power Requirement	



Power Connector	Lockable DC Jack
Power Requirement	+12V ~ +26V
ACPI	Single Power ATX Support S0, S3, S4, S5 ACPI3.0 Compliant
Adapter	Input: 100 ~ 240Vac/ 50 ~ 60Hz Output: 60W Adapter (12V @ 5A Adapter) AC-DC Adapter
Panel	
LCD Size	15", 4:3
Display Type	XGA
Resolution	1024 x 768
Pixel pitch	0.297mm(H) x 0.297mm(V)
Luminance	400 cd/m ²
Contrast ratio	700
Viewing angle	70 (U), 70 (D), 80 (L), 80 (R)
Response time	16 ms
Backlight	LED
Touch Type	5 Wires resistive
Touch Light Transmission	80%
Touch Controller	Onboard USB touch (EETI)

+ Ordering

LPC-1531
Intel Atom™ SoC N3000 family Processor/4G DDR3L/2GLAN/COM/12~26V input/12V Adaptor

ACC-LPC-WiFiUSB-4R
USB WiFi 802.11 b/g/n Module w/ Antenna, Cable

ACC-ARM-D1R
VESA STAND, 75mm & 100 mm

ACC-ARM-D19R
VESA STAND, 75mm & 100 mm

ACC-LPC-15-PMT-02R
Back Panel Mount Kit for LPC-15 Series, w/IP-65