



SEPC-KA

Fanless Onboard AMD Embedded G-Series SOC Quad core Processor Tiny Box PC



- > Fanless Onboard AMD Embedded G-Series SOC Quad core GX-415GA 1.5GHz Processor Tiny Box PC
- > 1 x 204-Pin DDR3/DDR3L 1333/1600MHz SO-DIMM, Up to 16 GB
- > 1 x Display Port, 1 x HDMI
- > 1 x Realtek RTL8111G PCI-e Gigabit Ethernet
- > 1 x Mic-In, 1 x Line-Out
- > 4 x USB 2.0, 2 x USB 3.0
- > 1 x RS-232 (Pin 9 without power)
- > 1 x 2.5" Drive bay
- > 1 x SD card slot
- > 1 x CIR
- > 1 x S/PDIF
- > 1 x Line-out, 1 x Mic-in

+ Spec

System	
Processor	Onboard AMD Embedded G-Series SOC Quad core GX-415GA 1.5GHz Processor
System Memory	1 x 204-Pin DDR3/DDR3L 1333/1600MHz SO-DIMM up to 16 GB
Watchdog Timer	H/W Reset: 1sec. ~ 65535sec./min. and 1sec. or 1min./step
H/W Status Monitor	Monitoring CPU & System Temperature and Voltage
Board	SENX-KA
Expansion	
Expansion	1 x Mini PCI-e Supports mSATA 1 x Mini PCI-e
Storage	
Storage	1 x Mini PCI-e Supports mSATA 1 x 2.5" Drive Bay
I/O	
USB	4 x USB 2.0 2 x USB 3.0
COM Port	1 x RS-232
Other	1 x SD card slot 1 x SIM card slot 1 x Power on/off switch 1 x Power LED 1 x HDD LED 1 x SMA connector (optional) 1 x S/PDIF 1 x CIR
Display	
Chipset	AMD Embedded G-Series Integrated
Resolution	HDMI: 3840 x 2160 @ 24 Hz / 1920 x 1080 @ 60 Hz DP: 3840 x 2160 @ 24 Hz / 2560 x 1600 @ 60 Hz HDMI+ DP
Interface	HDMI DP
Audio	
Chipset	Realtek ALC892 Audio Codec supports 2-CH
Audio Interface	Mic-In and Line-Out
Ethernet	
Chipset	1 x Realtek RTL8111E
Ethernet Interface	10/100/1000 Base-Tx GbE compatible
Mechanical & Environmental	
Operating Temp	(w/SSD, mSATA), ambient w/ air flow 0°C ~ 50°C (32°F ~ 122°F) (w/HDD), ambient w/ air flow 0°C ~ 40°C (32°F ~ 104°F)
Storage Temp	-20°C ~ 75°C (-4°F ~ 167°F)
Operating Humidity	0% ~ 90% Relative Humidity, Non-condensing
Construction	Aluminum + Metal
Mounting Kit	VESA Mount kit (Optional)
Dimension (L x W x H)	180 x 125.2 x 53 mm
Power Requirement	
Power Connector	DC Jack
Power Requirement	+12V
Power Mode	ATX



Adapter

Input: 100 ~ 240Vac/ 50 ~ 60Hz
Output: 60W Adapter (12V @ 5A)

+ Ordering

SEPC-KA-A1R
Fanless Onboard AMD Embedded G-Series SOC Quad core Processor Tiny Box PC