


4.0 ± 0.5



B-B 4.0

Ø2.0

340 (Out Line)
338 (Glass)
302 (Viewable Area)
297 (Active Area)

514 (Out Line)
511 (Glass)
480 (Viewable Area)
476 (Active Area)

Sensor1

Sensor2

Sensor3

Sensor4

4-R2.0

600 ± 10


Ø3

I Direction

Ø6.00 ± 0.50



A-A



I Direction

I Direction		
PIN	Signal	Insulation Color Overall Shield
1	Overall Shield	
2		
3	Y + Receive	BLUE
4	Y Transmit	BLUE
5	Y - Receive	BLACK
6	Y Ground	YELLOW
7	Shield	
8	X Ground	GREEN
9	X+Receive	WHITE
10	X Transmit	RED
11	X-Receive	RED
12		

sensor 1	Y-Transmit
sensor 2	Y-Receive
sensor 3	X-Receive
sensor 4	X-Transmit

Product Requirement:
Glue line way: on the bevel edge

Unmarked Tolerance							SAW screen specs			
from (mm)	to (mm)	Quality Level	mark	Content of Amendment	Edition	Author	Date	sign	weight	Scale
0	10	±0.05								
10	50	±0.10	Design		standard					Free
50	100	±0.15	Drawing		process					
100	200	±0.20	Check		Approve					

mark

sign weight Scale

Free

Total X 1 P X 1 P

product CTB220C-4K

Drawing No.

product
Dugan Choudh Electronic co., Ltd.